

CORDLESS BRUSHLESS RECIPROCATING SAW 18V**Product description**

HT2E234-0RS: An efficient tool for fast cutting under heavy load of various materials, such as wood, metal, plastics. Perfect for construction and renovation works. The rotational speed of 0-3000 RPM and the saw blade stroke of 28 mm allow for faster and effective work. Smooth change of rotational speed and a large range of adjustment of foot length and tilt give full control over the cutting activity. The brushless motor with its innovative design, thanks to the elimination of brush friction and special magnets, ensures greater power, longer operating time, and durability of the power tool. Advanced electronic systems constantly regulate the motor operation, optimising its power for the activity being performed, which translates into operational efficiency and maximization of battery operating time. The engine is protected against dust, metal particles and seizure. Tool-free assembly ensures a quick and easy blade replacement. The metal gearbox increases wear resistance and ensures the precision of the mechanism. Thermal protection protects the device against overheating during operation. The soft grip handle enables a more secure grip on the power tool and dampens vibrations during work. Rubber bumpers protect the device from mechanical damage. A powerful built-in LED torch perfectly illuminates the cutting area. The OneAccuSystem 18V enables the battery of your choice to be used in a wide and varied range of power tools for the toughest jobs. HT2E242-C60: An efficient charger that will charge a 2 Ah battery in just approx. 30 min. An advanced electronic module monitors battery voltage and temperature to maximise the efficiency of the charging process and ensure long battery life. Overheating protection extends the use life and battery life. Current short circuit protection improves the safety of the charging process. Monitoring the charge level of the cells extends their life. Indicators show the battery status and inform about the charging process. HT2E240-A40: Perfectly balanced in terms of low weight, small size, and capacity, a rechargeable battery for many different tools offered by the brand. An advanced electronic module monitors battery operation to maximize performance, operating time, increase durability and safety. Cell overheating protection, extending their operating time and enhancing their durability. Short circuit protection increases safety of work and storage of the rechargeable battery. Charging level control extends the life cycle of the cells. Cells made in the latest lithium-ion (Li-Ion) technology ensure high energy efficiency, robustness and reliability. Housing protected with rubber bumpers protects against mechanical damage. Cell protection against moisture. Operation possible from - 18 °C of external temperature, extends the scale of tool use. Charging level shows the available energy.

Characteristics

HT2E234-0RS:

- Foot length adjustment.
- Foot tilt angle adjustment.
- Tool-free handle.
- Rotational speed: 0-3000 RPM.
- Blade stroke: 28 mm.
- Tool-free blade holder.
- Maximum thickness of wood to be cut - 150 mm.

- Brushless motor Metal gearbox housing.
- Metal gear mechanism.
- LED light Smooth speed regulation.
- Anti-vibration soft grip handle.
- Protective rubber bumpers.
- Motor protection against dust, metal particles and seizure.
- Overheating protection.
- Weight 3.22kg.
- Battery to be purchased separately.
- 3-year warranty upon registration of the device.
- OneAccuSystem.
- Voltage 18 V.

HT2E242-C60:

- Voltage 18 V.
- Current 4A.
- Weight 0.56kg.
- Protections - overheating, overcharging, short circuit.
- Charging process indicator.
- Charging time 80 % of a 2 A battery - 30 min.
- Charging time 80 % of a 4 A battery - 60 min.
- Charging time 80 % of a 6 A battery - 90 min.

HT2E240-A40:

- Li-Ion technology.
- Voltage – 18 V.
- Capacity – 4.0 Ah.
- Weight – 0.67 kg.
- Protection against overheating, overcharging, short circuit.
- Charging level.
- EAN code – 5902801489785.

Technical data

			
HT2E252-B14RS	5902801490484	0	

Höbert Technik GmbH, Pariser Platz 6a, 10117 Berlin, Deutschland
 Producent/ Manufacturer/ Hersteller/ Произведено для:
 PL GTV Poland S.A., ul. Przejazdowa 21 05-800 Pruszków, Polska/ Poland/ Polen/ Польша
 Importer/ Импортёр:
 HR GTV Croatia d.o.o.; Kovinska 4s, 10000 Zagreb, Hrvatska
 Distributor:
 ES GTV España Herrajes, E Iluminación, S.L., Avenida Aragón 308, 46021 Valencia, Spain
 CZ GTV Czech Distribution s.r.o., CTPark Ostrava, Na Rovince 879, 720 00 Ostrava Hrabová