



Nitrile

An unparalleled combination of chemical splash protection, comfort and durability

- The world's leading disposable glove for chemical splash protection
- Made with TNT Chemical Splash Resistance Technology for superior protection against harmful chemical splashes
- Super soft nitrile provides a comfortable, silky feel for extended wear
- Proprietary formulation provides robust durability in a softer glove
- Silicone-free design is paint and finish process friendly




Industries

- Life Sciences
- Food Processing
- Automotive
- Machinery and Equipment
- Chemical
- Agriculture
- Utilities
- Warehousing

Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Meat, Fish and Food Processing
- Industrial Production
- Maintenance
- Laboratory analysis
- Chemical Handling



TECHNICAL DATA SHEET

PRODUCT INFORMATION

	92-600
Material	Nitrile
Color	Green
Glove Design	Powder-Free, Chlorinated, Silicone Free, Smooth
Cuff	Beaded
Manufacturing/QMS Audit Standards	ISO 9001
Regulatory	Category III, EAC TP TC 019:2011, EN 374:2003, EN ISO 374-1:2016, EN 420:2003 + A1:2009, EN ISO 374-5:2016, FDA21 CFR 177-2600-US Food Contact Approved, Food Type: Rubber, ISO 9001
Packaging	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia, Sri Lanka, Thailand
User Needs Segment	Robust
Available sizes	S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
Anti-static	Yes

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767, EN 420
Freedom from Holes (Inspection level I)	4.0 AQL (North & South America) / 1.5 AQL (Europe, Middle East, Africa, Asia, Pacific)		ASTM D5151, EN 455-1
Palm Thickness (mm/mils)	0.125 / 4.9		ASTM D3767, EN 420
Finger Thickness (mm/mils)	0.14 / 5.5		ASTM D3767, EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 18	≥ 18	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥ 6	≥ 6	EN 455-2

ORDERING INFORMATION


Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	92600070	92600080	92600090	92600100

Technology



Performance Standards and Regulatory Compliance

For additional information visit us at www.ansell.com, or call us at



Europe, Middle East & Africa Region
 Ansell Healthcare Europe NV
 T: +32 (0) 2 528 74 00
 F: +32 (0) 2 528 74 01

North America Region
 Ansell Healthcare Products LLC
 T: +1 800 800 0444
 F: +1 800 800 0445

Australia
 Ansell Limited
 T: +61 1800 337 041
 F: +61 1800 803 578

Asia Pacific Region
 Ansell Global Trading Center
 (Malaysia) Sdn Bhd
 T: +603 8310 6688
 F: +603 8310 6699

Latin America & Caribbean Region
 Ansell Commercial Mexico S.A. de C.V.
 T: +52 442 248 1544 / 248 3133

Russia
 Ansell PYC
 Ten. +7 495 258 13 16