



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## ARDON® PETRAX DOUBLE

MULTIFUNCTIONAL HANDLING IN DRY AND WET ENVIRONMENTS  
WITH THE POSSIBILITY OF HEAT PROTECTION



EN 388: 2016



EN 407: 2004

TECHNICAL DATA



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® PETRAX DOUBLE

MULTIFUNCTIONAL HANDLING IN DRY AND WET ENVIRONMENTS  
 WITH THE POSSIBILITY OF HEAT PROTECTION

**CODE**                      **A8107**

**MATERIAL**

Lining                      15G polyester  
 Coating                    ¾ latex (red) + ½ latex foam (black)  
 Thickness                 1,4 mm (in palm)

**SIZE(S)**                    7 / S – 11 / 2XL

**UNIT**                        pair

**PACKING**


Units in carton            240 pairs → 120 pairs *change of cardboard in 2. ½ 2022*  
 Units in polybag         12 pairs  
 Retail packaging         sales label

**DIMENSIONS**

	5	6	7	8	9	10	11	12
Carton H x W x D (cm)	-	-	43x27x34	43x27x34	43x27x34	43x28x35	43x28x35	-
Carton (cbm)	-	-	0,0395	0,0395	0,0395	0,0421	0,0421	-

**WEIGHT**

	5	6	7	8	9	10	11	12
Carton (kg)	-	-	8,60	9,50	10,2	10,9	11,6	-
Unit (g)	-	-	55,0	62,0	68,0	74,0	80,0	-



**Size chart (cm)**

	5	6	7	8	9	10	11	12
Total length (A)	-	-	23,0	24,0	25,0	26,0	27,0	-
Cuff length (B)	-	-	7,10	7,30	7,50	7,70	7,90	-
Cuff width (C)	-	-	7,80	8,00	8,20	8,40	8,60	-
Palm width (D)	-	-	9,80	10,3	11,0	11,2	11,5	-

Tolerance (A) ± 0,50 (cm)  
 Tolerance (B) ± 0,70 (cm)

Tolerance (C) ± 0,70 (cm)  
 Tolerance (D) ± 0,70 (cm)

**DESCRIPTION**

Comfortable knit with double latex dipping, waterproof and with a secure grip.

TECHNICAL DATA




**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## STANDARDS


(EU) 2016/425

**EN ISO 21420:2020** Protective gloves – general requirements and test methods

**EN 388:2016 + A1:2018** Protective gloves against mechanical risks

PROTECTION LEVELS		LVL	score	unit
 <p><b>EN 388</b></p>	<b>MECHANICAL RISKS</b>			
	abrasion resistance	2	500 – 2.000	cykles
	cut resistance	1	1,2 – 2,5	index
	tearing resistance	4	> 75	N
	puncture resistance	1	20 – 60	N
cut resistance acc. to ISO	X	not measured	N	

**EN 407:2004** Protective gloves against heat or flame

PROTECTION LEVELS		LVL	score
 <p><b>EN 407</b></p>	<b>THERMAL RISKS</b>		
	resistance to burning	X	not measured
	resistance to contact heat	2	250°C for 15s
	resistance to convective heat	X	not measured
	resistance to radiant heat	X	not measured
	resistance to small drops of molten metals	X	not measured
	resistance to large drops of molten metals	X	not measured

### SPECIAL FEATURES

- functional double dipping:
  - the base layer of smooth latex acts as a barrier against liquids
  - outer layer of latex foam allows a secure grip (even on wet objects)
- for work in both dry and wet environments, for example with loose mixtures with water (building mixtures, mortar, paints, etc.)
- protection against heat up to 150 ° C (according to certification up to 250 ° C for 15 seconds, but we generally do not recommend exposure to temperatures higher than 150 ° C, during which latex secondary vulcanizes and heats up)
- mandatory information on inner label = ARDON® design
- each pairs in each size is retail ready packed

TECHNICAL DATA



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

**Retail packaging (with sales label)**

A8107/07

A8107/08

A8107/09

A8107/10

A8107/11

**EAN**

8592390012814

8592390075611

8592390075628

8592390075635

8592390041685

TECHNICAL DATA





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**



TECHNICAL DATA